

# DENSURF SM 101

## Surface Modifier

### PRODUCT DESCRIPTION

DENSURF SM 101 is a surface modifier developed for solvent-based, solvent-free and water-based coatings.

- Enhances the wetting and spreading of paint by reducing the surface tension of the coating.
- Prevents the surface defects such as Benard cell, crater and orange peel effect.

### APPLICATIONS

- Architectural Coatings
- Floor Coatings
- Protective Coatings
- General Industrial Coatings
- Automotive Coatings
- Printing Inks
- Wood Coatings

### SOLUBILITY

Water	<input type="radio"/>	Aliphatic Hydrocarbon	<input checked="" type="radio"/>
Ethyl Alcohol	<input checked="" type="radio"/>	Butyl Acetate	<input checked="" type="radio"/>
Butyl Alcohol	<input checked="" type="radio"/>	Xylene	<input type="radio"/>
Acetone	<input type="radio"/>	Butyl Glycol	<input checked="" type="radio"/>
Butyl Glycol Acetate	<input type="radio"/>		
<input checked="" type="radio"/> Soluble	<input type="radio"/> Partly Soluble	<input type="radio"/> Not Soluble	

### STORAGE

- Store between 5°C-35°C.
- The shelf life is at least 60 months in the unopened original packaging from the date of manufacture when stored at recommended conditions.
- Close the packaging cap tightly after use.
- WARNING! Keep away from acids, heat and moisture.

### TECHNICAL PROPERTIES

- Chemical Structure: Polyether modified polysiloxane
- Solid Content(10min., 160 °C): 96 ±2%
- Appearance: Clear/Light yellow liquid
- Ionic Structure: Non-ionic
- Density (20 °C): 1.037 ±0.020 g/ml

### SYSTEMS

Emulsion Resins	<input checked="" type="radio"/>	Water-borne Resins	<input checked="" type="radio"/>
Solvent-based Resins	<input checked="" type="radio"/>	Solvent-free Resins	<input checked="" type="radio"/>
<input checked="" type="radio"/> Suitable	<input type="radio"/> Partly Suitable	<input type="radio"/> Not Suitable	

### DOSAGE

Recommended amount; 0.05-0.50% (by weight as supplied based on total formulation)

*Note: Amounts mentioned above are just a recommendation. Please make laboratory tests to specify the optimum amounts.*

### PROCESS RECOMMENDATION

- Product can be incorporated during any stage of the production process.
- It can be diluted with suitable solvent.
- Dilution is recommended to make dosing easier.
- Recommended to test foam formation of the product and overcoat adhesion of the system.